



"They'll Look Like New Forever."

JOINT-LOCK SAND™ PAVER FINISHING SAND



1. PRODUCT NAME: JOINT-LOCK PAVER FINISHING SAND

2. ITEMS:

- 70 LB. JOINT-LOCK SAND BROWNSTONE
- 70 LB. JOINT-LOCK SAND GRAYSTONE
- 70 LB. JOINT-LOCK SAND SANDSTONE

3. DISTRIBUTED BY:

CAMBRIDGE PAVERS, INC.
Jerome Ave • PO Box 157
Lyndhurst, NJ 07071.0157
TEL: 201.933.5000
FAX: 201.933.5532
www.cambridgepavers.com

4. PRODUCT DESCRIPTION:

Joint-Lock Sand is a polymer modified paver finishing sand that is specifically designed to complement and enhance any paver installation. Joint-Lock sets hard to resist weed growth, insect mining and erosion. It will resist scouring caused by sweeping, water rinsing and traffic.

Joint-Lock Sand is a uniformly blended mixture of top quality mason-grade sand and a polymeric additive. When activated (by water), the polymer allows Joint-Lock Sand to firm up in the joints between paving stone pavers. It forms a firm barrier - like a one-piece flexible joint. This barrier cannot disappear into the soil, it cannot be blown away, it stays in place between the blocks or bricks. Joint-Lock will help the pavement installation resist movement and prevent water infiltration into the paver base.

It is sold in 70 Lb. (31.7kg) bags / 42 per pallet by nurseries, landscape yards, mason material yards and home centers.

5. TECHNICAL DATA:

Complete installation instructions can be found on the Joint-Lock bag. Only use Joint-Lock Sand for joints 1/2" or less. Joint-Lock is not recommended for sloping grades greater than 5%.

POLYMERIC PAVER FINISHING SAND

6. INSTALLATION INSTRUCTIONS:



1. CLEAN & DRY PAVERS

Make sure that the surface of the pavers and the paver joints are free of debris and completely dry before applying Joint-Lock Sand. The weather forecast should be rain free for 12 hours after application to ensure optimum bonding and product performance.



2. POUR SAND & SPREAD

Pour Joint-Lock Sand evenly over the entire area to be finished. Sweep Joint-Lock Sand repeatedly over the joints until they are completely and uniformly filled. For best results fill joints to the full depth of the pavers. **DO NOT USE A FILLER SAND AS IT WILL COMPROMISE THE STRENGTH OF THIS PRODUCT.**



3. COMPACT & SWEEP

Use a gas powered plate compactor to compact the sand between the joints of the pavers. This will ensure all voids are filled, repeat steps 2 & 3 as necessary. After compaction sweep off all extra sand. If pavers are coarse, use a leaf blower on lowest setting to clear sand off the paver surface.



4. FLOOD AREA & DRY

After surface of pavers is completely free of sand begin to lightly but thoroughly flood the paving stones with water. Allow the water to collect and seep into the paver joints. Repeat this step 3 times allowing 10 minutes between soakings. Make sure the paving stones are free of car and foot traffic for 18-24 hours following application of Joint-Lock Sand.

7. CAUTION:

KEEP UNUSED JOINT LOCK SAND DRY! Do not apply if rain is forecast within 12 hours of the application or the temperatures are expected to go below freezing. If treating an existing walkway, patio, or previously laid pavers, make sure the joints are clean and free of debris, preferably to the base of the paving stone but at least to a depth of 1" below the surface of the pavers.

8. SAFETY AND HANDLING:

Always wear dust masks, goggles, and gloves while using Joint-Lock Sand. If the product comes in contact with eyes, rinse them thoroughly with water. **KEEP OUT OF REACH OF CHILDREN**

9. WARRANTY:

Seller warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is LIMITED to the replacement of this product (as purchased) found to be defective or, at the shipping company's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Package Pavement in writing. This limited warranty is issued and accepted in lieu of all other express warranties and excludes liability for consequential damages.

www.cambridgepavers.com

